NUCLEAR SCIENCE AND TECHNIQUES 26, 050103 (2015)

Proposal for a high brightness γ **-ray source at the SXFEL***

WU Hai-Long (武海龙),^{1,2} CHEN Jian-Hui (陈建辉),^{1,†}

LIU Bo (刘波),¹ WANG Dong (王东),¹ and ZHAO Zhen-Tang (赵振堂)¹

¹Shanghai Institute of Applied Physics, Chinese Academy of Sciences, Shanghai 201800, China

²University of Chinese Academy of Sciences, Beijing 100049, China

(Received April 4, 2015; accepted in revised form August 18, 2015; published online October 20, 2015)

High brightness γ -rays produced by laser Compton scattering (LCS) are ideal probes for the study of nucleon and nuclear structure. We propose such a γ -ray source using the backscattering of a laser from the bright electron beam produced by the linac of the Shanghai Soft X-ray Free-electron Laser (SXFEL) test facility at the Shanghai Institute of Applied Physics (SINAP). The performance is optimized through theoretical analysis and benchmarked with 4D Monte-Carlo simulations. The peak brightness of the source is expected to be larger than 2×10^{22} photons/(mm² mrad² s 0.1%BW) and photon energy ranges from 3.7 MeV to 38.9 MeV. Its performance, compared to Extreme Light Infrastructure-Nuclear Physics (ELI-NP), and the Shanghai Laser-Electron Gamma-ray Source (SLEGS), is given. The potential for basic and applied research is also briefly outlined.

Keywords: High brightness γ -ray source, Laser Compton scattering (LCS), Soft X-ray Free-electron Laser (SXFEL)

DOI: 10.13538/j.1001-8042/nst.26.050103

I. INTRODUCTION

Over the past decades, with remarkable advancements in the fields of high intensity lasers and high brightness electron beams, laser Compton scattering (LCS) light sources [1], based on a process in which relativistic electron beams scatter lasers to produce quasi-monochromatic X-rays or γ -rays, have found a broad range of applications. At photon energies below 100 keV, although storage ring light sources [2] and X-ray free electron lasers [3] can produce X-rays at higher brightness, LCS light sources offer attractive, complementary capabilities at a smaller fraction of the cost and size [4] for medical applications [5–9]. At γ -ray photon energies, LCS light sources will produce the highest brightness, enabling a variety of applications [10-14], including nuclear physics [10–13], nuclear astrophysics [11], polarized positron beams [15], polarized neutron beams [16], production of medical radioisotopes [17], nondestructive detection of radioactive isotopes [18], assay of nuclear materials [18], etc.

Although the Compton effect was discovered in the early 1920's by A. H. Compton as his Nobel-Prize-winning work, it was not until 1960's that a method of very high energy γ -rays via the LCS process in charged particle accelerators was proposed independently by Milburn [19], and Arutyunyan and Tumanyan [20]. While a number of successful demonstrations of the LCS concept have been made through the years, the γ -ray yield was quite low [21–23]. In 1978 the first γ -ray LCS facility, the Ladon project, was brought into operation in Frascati [24]. It was followed by several new LCS γ -ray facilities, including LEGS@NSLS[25] and HI γ S@DFELL

in the US [26], GRAAL@ESRF in France [27], ROKK in Russia [28], and LEPS@SPring-8 in Japan [29, 30]. Among these facilities, Ladon, LEGS, and GRAAL were decommissioned in 1993, 2006, and 2008, respectively, HI_YS and LEPS are still active for low energy nuclear structures, nuclear astrophysics, and hadron physics studies. There is still growing interest in building new γ -ray facilities in storage ring light sources, e.g., LCS γ -ray sources at the TERAS [31], SAGA [32], UVSOR-II [33], LEPS2 [35], and NewSUB-ARU [34] in Japan. The HI γ S team also proposed the HI γ S2 project [36] to further increase the photon flux. Some newly built 3rd generation light source facilities are also pursuing to integrate γ -ray sources in their storage rings, e.g. PLS in Korea [37], ALBA in Spain [38], CLS in Canada [39], MAX-IV in Sweden [40], DA Φ NE at LNF-INFN in Italy [41], and SSRF in China [42].

With the introduction of a photocathode radio-frequency (RF) electron gun, the linac electron beam quality has been improved dramatically during the last decades. As pointed out in Ref. [43], linac based LCS light source holds great promise for compact X-rays. There are currently many efforts all over the world for the development of such kind of X-rays, e.g. ATF at BNL [44] and PLEIADES at LLNL [45, 46] in the US, PHOENIX at HZDR in Germany [47], AIST at ETL [48], LUCX [49] and STF [50] at KEK in Japan, TTX at Tsinghua University [51] in China, and etc. For the γ -ray energies, colliding lasers with high quality electron beam from linac offers opportunities for generation of γ -rays with an exceptionally narrow spectral width (< 0.1%) for photo-nuclear experiments, especially to conduct nuclear resonance fluorescence experiments [52, 53]. LLNL made an important step forward, producing a mono-energetic MeV-level γ -ray source [54, 55], enabling entirely new isotope-specific applications of importance to material science, medicine, industry, and engineering, which opens up a new era of nuclear photonics [14, 56-58]. With its great success, X-band techniques based on the MEGa-ray project [59, 60] at LLNL is under development. It is followed by the Extreme Light Infrastructure-Nuclear

^{*} Supported by the Major State Basic Research Development Program of China (No. 2011CB808300), the Shanghai Natural Science Foundation (No.13ZR1464700), and the Knowledge Innovation Project of the Chinese Academy of Sciences (No. 255015061)

[†] Corresponding author, chenjianhui@sinap.ac.cn



Fig. 1. (Color online) Schematic layout of the SXFEL project.

Physics (ELI-NP) project [61, 62], a major facility of the Nuclear Physics Long Range Plan in Europe [63]. ELI-NP, now under construction in Bucharest-Magurele, Romania, will be one of the three pillars of ELI and will consist of two components: a very high intensity laser beam and a very intense $(10^{13} \gamma/s)$, brilliant γ beam, 0.1% bandwidth, with γ photon energy up to 19 MeV, which will create a new European laboratory with a broad range of science covering the frontier of fundamental physics, new nuclear physics and astrophysics as well as applications in diverse fields.

In this paper, we propose a high brightness, narrow bandwidth γ -ray source by using the high brightness electron beam from the linac of the Shanghai Soft X-ray Free-electron Laser (SXFEL) facility [64]. The main parameters of SXFEL will be described in Sec. II. In the following Section, the analytical optimization benchmarked with 4D Monte-Carlo simulations will be presented. Its performance will be compared to ELI-NP and the Shanghai Laser Electron Gamma Source (SLEGS). The potential opportunities offered by combining bright X-ray and γ -ray will be briefly outlined. Some concluding remarks will be given in the last section.

II. SHANGHAI SOFT X-RAY FREE-ELECTRON LASER TEST FACILITY

The SXFEL test facility is currently under construction in the SSRF campus, with the primary purpose of delivering fully coherent radiation at the wavelength of about 8.8 nm. With energy upgraded to 1.3 GeV, it is possible to push the X-ray wavelength down to the water window (\sim 3 nm) and even the magnetic window (\sim 1 nm). As shown in Fig. 1, this facility is based upon an electron linac, composed of a photoinjector, hybrid S-band and high gradient C-band accelerators, and 2 bunch compressors. The X-ray FEL is produced in a two-stage cascaded harmonic generation undulator system, and its performance is characterized in the X-ray transport and diagnostic system at the end. The main parameters of SXFEL is shown in Table 1.

III. PROPOSAL FOR A HIGH BRIGHTNESS γ -RAY SOURCE AT THE SXFEL

A. Basic considerations

As previously mentioned, the narrow bandwidth and high brightness γ -ray source has been long cherished by many re-

TABLE 1. Main parameters of the SXFEL project.

Parameters	Baseline	Upgrade	Unit
e- beam energy	0.84	1.3	GeV
e- energy spread	< 0.15%	< 0.15%	
e- bunch charge	0.5	0.5	nC
e- normalized emittance	<1.5	<1.5	mm mrad
e- pulse length (FWHM)	<1	< 1	ps
e- beam current	500	500	A
e- repetition rate	10	10	Hz
FEL wavelength	8.8	3	nm
FEL power	>100	>100	MW
FEL pulse length	<150	<150	fs

search fields. We propose here to build a high brightness γ -ray source using the LCS mechanism based on the SXFEL linac with the energy of the electron beams ranging from 400 to 1300 MeV. As shown in Fig. 1, the γ -ray source will be located at the 2nd branch, and the colliding laser will share the same laser hutch of the seed laser of SXFEL.

We chose head-on interaction geometry to make the overlap between the electron and the laser beam larger. This source is capable to produce photon energies ranging from 3.7 MeV to 38.9 MeV of γ -rays through a Doppler up-shift of 800 nm Ti: Sapphire laser beams by a factor of $4\gamma^2 E_L/(1 +$ $4\gamma^2 E_L/E_e$). In order to obtain a narrow bandwidth photon beam, we should study a variety of factors which may have impact on the γ -ray spectrum. For realistic laser-electron interactions, the laser and electron beams at the interaction point have their intrinsic divergences and energy spreads. These non-ideal factors determine the bandwidth of the scattered photon beam. The relative energy spread of the scattered photons generated by the electron beam energy spread is quite simple, $\Delta E_{\gamma}/E_{\gamma} = 2\Delta E_e/E_e$; by which the laser is natural bandwidth is the same as the laser bandwidth, $\Delta E_{\gamma}/E_{\gamma} = \Delta E_{\lambda}/E_{\lambda}$; by the intrinsic divergence of the electron beam scales as, $\Delta E_{\gamma}/E_{\gamma} = [\varepsilon_n/r_e]^2$, where ε_n and r_e are the normalized emittance and beam radius of the electron beam, respectively. The nonlinear effect associated with the laser intensity will also cause spectral broadening due to the inhomogeneous pondermotive forces during the course of the laser pulse changes in the electron's longitudinal velocity and leads to a variable redshift during scattering [65-74]. As pointed out in Ref. [71-73], even in the so-called nonrelativistic regime, nonlinear effects may become significant if the pulses become relatively long. These nonlinear effects yield important spectral broadening.

In summary, for the analytical optimization of the perfor-

mance of the γ -ray source, the main goal is to maximize the on-axis spectral brightness and to reduce the bandwidth and related parameters, including the beam size, emittance of the electron beam, and the beam size, pulse duration of the laser beam. Hereafter, we assume that the pulse energy of the laser is limited to 100 mJ. The performance optimization is based on theoretical work by Hartemann *et al.* [71–73, 75] and Petrillo *et al.* [74, 76], as well as MC simulation code

developed by Luo [77].

B. Performance optimization: linear and nonlinear regime

It's found [75] that in the linear regime the peak on-axis brightness is,

$$\hat{B}_{x} = \frac{4 \times 10^{-15}}{\pi^{2}} \frac{\gamma_{0}^{2}}{\varepsilon^{2}} \frac{N_{e} N_{\lambda}}{\Delta \tau} \frac{r_{0}^{2}}{w_{0}^{2}} \frac{\eta e^{1/\mu^{2}} \left[\Phi(1/\eta) - 1\right] - \mu e^{1/\mu^{2}} \left[\Phi(1/\mu) - 1\right]}{\mu^{2} - \eta^{2}} \\ \cdot \exp\left[\frac{\chi - 1}{2\chi \Delta u_{\perp}^{2}} \left(2 + \frac{\delta \omega^{2} + \delta \gamma^{2} \chi^{2}}{2\chi(\chi - 1)\Delta u_{\perp}^{2}}\right)\right] \left[1 - \Phi\left(\frac{\chi - 1}{\sqrt{\delta \omega^{2} + \delta \gamma^{2} \chi^{2}}} \left[1 + \frac{\delta \omega^{2} + \delta \gamma^{2} \chi^{2}}{2\chi(\chi - 1)\Delta u_{\perp}^{2}}\right]\right)\right],$$
(1)

where $N_e = q/e$ is the number of electrons in the bunch, $\Delta \tau$ is the bunch duration, ε is the normalized emittance, γ_0 is beam energy, and $\delta \gamma$ is the energy spread. $N_{\lambda} = W/(\hbar \omega_0)$ is the total number of photons in the laser pulses, w_0 is the 1/e focal radius, $r_0 = 2.82 \times 10^{-15}$ m is the classical electron radius, and $\Phi(x) = (2/\sqrt{\pi}) \int_0^x e^{-t^2} dt$ is the error function. $\mu = c\Delta t/2\sqrt{2}z_0$ is the normalized inverse Rayleigh length and $\eta = \varepsilon/(\gamma_0 r_b^2)c\Delta t/2\sqrt{2}$ is the normalized inverse

beta function, where r_b is the radius at the focus of electron beam, Δt is the laser pulse duration, and $z_0 = \pi w_0^2 / \lambda_0$ is the Rayleigh length. $\chi = \omega_x / 4\gamma_0^2 \omega_0$ is the normalized upshifted frequency and $\delta \omega = \Delta \omega / \omega_0$ is the relative spectral width of laser pulse.

In the nonlinear regime, when spectral broadening induced by the inhomogeneous laser pondermotive force during the interaction is considered, the brightness reads,

$$\hat{B}_{x} = \frac{4 \times 10^{-15}}{\pi^{3}} \frac{\gamma_{0}^{2}}{\varepsilon^{2}} \frac{N_{e} N_{\lambda}}{\Delta \tau} \frac{r_{0}^{2}}{w_{0}^{2}} \int_{-\infty}^{\infty} \frac{e^{-\bar{z}^{2}} d\bar{z}}{(1+\eta^{2} \bar{z}^{2})(1+\mu^{2} \bar{z}^{2})} \exp\left[\frac{\chi \rho(\bar{z}) - 1}{2\chi \rho(\bar{z}) \Delta u_{\perp}^{2}} \left(2 + \frac{\delta \omega^{2} + \delta \gamma^{2} \chi^{2} \rho^{2}(\bar{z})}{2\chi \rho(\bar{z})(\chi \rho(\bar{z}) - 1) \Delta u_{\perp}^{2}}\right)\right] \\ \cdot \left[1 - \Phi\left(\frac{\chi \rho(\bar{z}) - 1}{\sqrt{\delta \omega^{2} + \delta \gamma^{2} \chi^{2} \rho^{2}(\bar{z})}} \left[1 + \frac{\delta \omega^{2} + \delta \gamma^{2} \chi^{2} \rho^{2}(\bar{z})}{2\chi \rho(\bar{z})(\chi \rho(\bar{z}) - 1) \Delta u_{\perp}^{2}}\right]\right)\right],$$
(2)

where $\rho(\bar{z}) = 1 + A_0^2 e^{-\bar{z}}/2(1 + \mu^2 \bar{z}^2)$, with A_0 being the maximum laser normalized vector potential.

At a given beam emittance, while tight focal size of the electron beam will cause a significant broadening of the spectrum, loosening the spot size can produce a narrower spectrum, but will decrease the overall spectral brightness of the source due to reduced electron density. It's therefore an optimum beam size for the highest γ -ray beam brightness that can be found. With the normalized emittance equal to 1.5 mm mrad (see Table 1), Figure 2 shows the peak spectral brightness for four different values of the electron beam focal radius: 5, 15, 20 and 25 µm. The spectral broadening due to a large divergence for a small beam size is clearly shown. Figure 3 shows the peak spectral brightness as a function of the electron beam focal radius with/without the nonlinear spectral broadening effect. One can see that the brightness variation as the electron beam size is not very sensitive, since it depends on the combined effects of divergence induced spectral broadening and the laser-e beam overlap integral. In order to achieve narrower bandwidth, we prefer to use a relatively

large electron beam size, as shown in Fig. 2. Therefore, $20 \,\mu m$ is chosen as the working value of the e-beam size.



Fig. 2. (Color online) Peak spectral on axis brightness for different electron beam sizes.

As the scaling laws (Eq. (1) and Eq. (2)) suggest, the peak spectral brightness of LCS light sources is proportional



Fig. 3. (Color online) Peak brightness as a function of the electron beam focal radius (blue: linear, black: nonlinear).

to the electron beam brightness. For a fixed beam size, large emittance means large divergence, and the divergenceinduced spectrum broadening decrease the peak brightness rapidly. Moreover, reducing the beam emittance to around 0.5 mm mrad, the peak brightness would be increased by a factor of ~ 3 .



Fig. 4. (Color online) Peak spectral on-axis brightness as a function of the normalized Doppler-shifted frequency. χ , and laser pulse duration, Δt .

In the case of Fourier-transform-limited laser pulses, the relation between the pulse duration, Δt , and the spectral bandwidth, $\Delta \omega$, satisfies: $\Delta \omega \Delta t = \sqrt{2}$. For large values of the laser pulse duration, the laser bandwidth is narrow, and the normalized vector potential is small, which allows for minimal linear and nonlinear spectral broadening. However, the overlap integral becomes small as the normalized parameters, η and μ , become large. Conversely, for ultrashort laser pulses, the fractional laser bandwidth contributes strongly to the spectral bandwidth, and nonlinear effects become important, further degrading the brightness. Peak spectral on-axis brightness as a function of the normalized Doppler-shifted frequency, χ , and laser pulse duration, Δt , are shown in Fig. 4 (nonlinear effect ignored) and Fig. 5 (nonlinear effect included). When nonlinear effects are neglected, a relatively large range of laser pulse durations yield high-brightness operations; the limits are set by the laser bandwidth for short pulses, which broaden the x-ray spectrum by diffraction for long pulses. Accounting for nonlinear effects, however, reveals a much tighter constraint on the drive laser pulse duration, as shown in Fig. 5, where the strength of the ponderomotive force is also indicated: the optimum lies in the range of 3–7 ps, and a duration of 5 ps would be a good working point.



Fig. 5. (Color online) Peak spectral on-axis brightness as a function of the normalized Doppler-shifted frequency. χ , and laser pulse duration, Δt . (Nonlinear effect included)

The size of the laser beams also have an impact on the laser normalized vector potential. The larger the laser beam size, the smaller the laser normalized vector potential, accordingly to reduce the nonlinear-induced spectral broadening. However, the larger the laser beam size, the smaller the laser photons density, and thus smaller photon flux and smaller the spectral brightness. Meanwhile, the Rayleigh length should be longer than the pulse duration. Small sizes will also introduce a large divergence. Figure 6 shows the peak spectral brightness as a function of the laser beam focal radius. We chose a laser spot size of 15 μ m as the working point.



Fig. 6. Peak spectral brightness as a function of the laser focal spot size.

PROPOSAL FOR A HIGH BRIGHTNESS

Through theoretical analysis, the optimized parameters of the electron beams and laser beams are finalized. To verify the predicted performance, numerical simulation is highly desirable. In SINAP, a four-dimensional (three-dimensional time and frequency-domain) Monte Carlo LCS simulation code, MCLCSS [77], has been developed with the Geant4 toolkit [78]. The code has the capability to calculate the spatial, spectral, and temporal characteristics of the LCS light sources with slanting collision configuration. The code has been benchmarked with the popular code, CAINS [79], and with realistic measurements by PLEIADES at LLNL, $HI\gamma S$ at Duke University and the UVSOR-II facility. As shown in Fig. 7, the simulation results agree reasonably well with theoretical predictions. A γ ray source with flux as high as 7×10^7 photons/s can be achieved with the optimized parameters of the electron and laser beam at the SXFEL project.



Fig. 7. (Color online) The peak spectral brightness of the γ -ray source at the SXFEL. (theory: blue line, MC simulation: red dots)

C. Comparison with ELI-NP and SLEGS

The SLEGS project [42, 80] is a LCS γ -ray source proposed at the storage ring of the SSRF. The SLEGS will be built at one of the long straight sections. There are two operational modes, intermediate energy mode with backscattering geometry, and low energy mode with side-scattering geometry. In the low energy mode, the interaction angle of the electron beam with the CO₂ incident laser can be changed continuously with a rotating platform, thus γ -ray photons with an energy mode of operation of SLEGS are listed in Table 2. Similarly, the optimized performance is shown in Fig. 8.

The performance comparison of ELI-NP and SLEGS is summarized in Table 3. Despite of the lower repetition rate, single bunch operation mode with around 3 order of magnitude lower spectral density, the flux per shot and peak brightness are comparable with ELI-NP, and are 2 orders of magnitude and 11 orders of magnitude higher than that of the SLEGS project, respectively.

TABLE 2. Main parameters of the SLEGS project.

1	1 5	
Parameters	Value	Unit
e- beam energy, E_e	3.5	GeV
e- energy spread, σ_{E_e}/E_e	0.944e-3	
e- beam current, I	300	mA
e- bunch charge, Q	0.864	nC
Bunch number	500	
e- emittance, $\varepsilon_x/\varepsilon_y$	2.59/2.59e-2	nm rad
e- beam size, σ_x/σ_y	276.9/12.24	μm
e- pulse length σ_z	3	mm
Laser wavelength, λ	10.64	μm
Laser Power, P	100	W
Laser spot size, σ_x/σ_y	50/50	μm



Fig. 8. (Color online) The peak spectral brightness of low energy mode of SLEGS. (theory: blue line, MC simulation: red dots)

D. Potential scientific opportunities

As aforementioned, the proposed γ -ray source at the SXFEL will be useful in diverse fields from nuclear structure physics [81-83] to nuclear isomers [84], nuclear astrophysics [85], and nuclear data [86], to space radiation effects research of aerospace electronic components, and accurate calibration of gamma detectors for aerospace. Moreover, by combining high brightness X-rays and γ -rays in a single facility, a number of opportunities for fundamental physics studies can be expected. For more than 30 years, photon colliders [87] have been considered as a natural additions to electron-positron collider projects in the high energy physics community. There has been renewed interest in recent years [88, 89] to build a photon collider as a Higgs factory, since the discovery of the Higgs boson in 2012. A new class of photon collider is proposed [90], in which a gammaray beam is fired into the high-temperature radiation field of a laser-heated hohlraum. In the SXFEL case, it fits quite well and provides more precise tools for the study of the Breit-Wheeler pair production process, which is the most striking prediction of quantum electrodynamics.

The possibility of creating a nuclear gamma-ray laser (NGL) has been attracting attention for half a century [91, 92]. However, as of now, convincing data about

WU Hai-Long et al.

THEE 5. FOR Market Comparison							
Parameters	LCS@SXFEL	ELI-NP [62]	SLEGS	Unit			
Photon energy	3.7-38.9	0.2 - 19.5	1.47-21	MeV			
Spectral density	4-39	$0.8 - 4 \times 10^4$	0.008 - 0.015	ph/(s eV)			
Bandwidth	< 0.5%	< 0.5%	< 0.5%				
Photons/shot within FWHM BW	$< 4.54 \times 10^{6}$	$< 2.6 \times 10^5$	< 0.00043	photons/pulse			
Photons/sec within FWHM BW	$< 4.54 \times 10^{7}$	$< 8.3 \times 10^{8}$	$< 1.5 \times 10^5$	photons/second			
Source size (rms)	12	10-30	275/12 (x/y)	μm			
Source divergence (rms)	0.8	0.03-0.2	0.6-0.9	mrad			
Peak brightness	$4 \times 10^{21} - 5 \times 10^{22}$	$10^{20} - 10^{23}$	$10^{11} - 10^{14}$	s.u.			
Pulse length (rms)	0.86	0.7 - 1.5	10.5	ps			
Repetition rate	10	100	347×10^6	Hz			

TABLE 3. Performance comparison

its experimental solution is still absent. The key conflict inherent in the NGL concepts is the antagonism between the necessity to accumulate a sufficient amount of excited nuclei and the requirement to narrow down the emission line to its natural radiative width. For the combined high brightness narrow bandwidth X/γ sources at SXFEL, it's possible to test the X-ray pumped NGL concept [93].

IV. CONCLUSION

In this paper, the design of a narrow bandwidth, high peak brightness LCS γ -ray source based on the SXFEL linac, is presented. Its peak brightness will be larger than 2×10^{22} photons/(mm² mrad² s 0.1%BW) and photon energy ranges from 3.7 MeV to 38.9 MeV, which will enable a broad range of nuclear physics studies and advanced nuclear photonics applications. The photon flux will be at least 2 orders of magnitude, and peak brightness will be 11 orders of magnitude higher than that of the SLEGS projects. Its performance is also comparable with the most advanced γ ray source, ELI-NP. By combing the brightness γ -rays with bright X-rays, a new type of photon collider for fundamental QED physics studies can be envisioned and the exploration of a new approach to γ -ray laser can be carried out.

It's also worthy to point out that current design studies are preliminary. There is still a lot of room for further improvement. To name a few, reduction of the emittance of the electron beam, adoption of the multi-bunch operation and the integration of the laser cavity [94], and the usage of plasma channels [95] may further increase the photon flux by orders of magnitude. Spectral broadening effects can be compensated by chirped electron beams [96], and/or suitable frequency modulation of incident laser pulses [97–99]. During the simultaneous operation of the X-ray FEL and the γ -ray source, the X/ γ -ray optics demanded by the aforementioned experiments will be technically challenging. These concerns will be the topics of our future studies.

ACKNOWLEDGMENTS

We appreciate the stimulating discussions with Prof. MA Yu-Gang, FANG De-Qing, WANG Hong-Wei, FAN Gong-Tao, and LI Yong-Jiang of Shanghai Institute of Applied Physics, Chinese Academy of Sciences.

- Krafft G A and Priebe G. Compton sources of electromagnetic radiation. Rev Accel Sci Tech, 2010, 3: 147–163. DOI: 10.1142/S1793626810000440
- [2] Zhao Z T. Storage ring light sources. Rev Accel Sci Tech, 2010, 3: 57–76. DOI: 10.1142/S1793626810000361
- [3] McNeil B W J and Thompson N R. X-ray free-electron lasers. Nat Photonics, 2010. 4: 814–821. DOI: 10.1038/nphoton.2010.239
- [4] Barletta W A and Borland M. Report of the basic energy sciences workshop on compact light sources, 2010.
- [5] Weeks K J. Radiation therapy potential of intense backscattered Compton photon beams. Nucl Instrum Meth A, 1997, 393: 544–547. DOI: 10.1016/S0168-9002(97)00561-5
- [6] Carroll F E. Tunable monochromatic X rays: A new paradigm in medicine. Am J Roentgenol, 2002, **179**: 583–590. DOI: 10.2214/ajr.179.3.1790583
- [7] Bech M, Bunk O, David C, *et al.* Hard X-ray phase-contrast imaging with the Compact Light Source based on inverse Compton X-rays. J Synchrotron Rad, 2009, 16: 43-47. DOI:

10.1107/S090904950803464X

- [8] Achterhold K, Bech M, Schleede S, *et al.* Monochromatic computed tomography with a compact laser-driven X-ray source. Sci Rep, 2013, 3: 1313. DOI: 10.1038/srep01313
- [9] Bech M, Tapfer A, Velroyen A, et al. In-vivo dark-field and phase-contrast X-ray imaging. Sci Rep, 2013, 3: 3209. DOI: 10.1038/srep03209
- [10] Schaerf C. Polarized gamma-ray beams. Phys Today, 2005, 58: 44–50. DOI: 10.1063/1.2062918
- [11] Weller H R, Ahmed M W, Gao H, *et al.* Research opportunities at the upgraded HIγS facility. Prog Part Nucl Phys, 2009, **62**: 257–303. DOI: 10.1016/j.ppnp.2008.07.001
- [12] Nedorezov V G, Turinge A A and Shatunov Yu M. Photonuclear experiments with Compton-backscattered gamma beams. Phys-Usp+, 2004, 47: 341–358. DOI: 10.1070/PU2004v047n04ABEH001743
- [13] Nedorezov V G. Experiments with Compton Back Scattered Gamma Beams (on GRAAL Collaboration Results). Phys Part Nuclei, 2012, 43: 326–347. DOI:

PROPOSAL FOR A HIGH BRIGHTNESS

10.1134/\$1063779612030057

- [14] Thirolf P G and Habs D. Bright perspectives for nuclear photonics. Eur Phys J-Spec Top, 2014, 223: 1213–1219. DOI: 10.1140/epjst/e2014-02175-1
- [15] Omori T, Fukuda M, Hirose T, *et al.* Efficient propagation of polarization from laser photons to positrons through Compton scattering and electron-positron pair creation. Phys Rev Lett, 2006, **96**: 114801. DOI: 10.1103/PhysRevLett.96.114801
- [16] Habs D, Gross M, Thirolf P G, *et al.* Neutron halo isomers in stable nuclei and their possible application for the production of low energy, pulsed, polarized neutron beams of high intensity and high brilliance. Appl Phys B, 2011, **103**: 485–499. DOI: 10.1007/s00340-010-4276-3
- [17] Habs D and Köstar U. Production of medical radioisotopes with high specific activity in photonuclear reactions with γ -beams of high intensity and large brilliance. Appl Phys B, 2011, **103**: 501–519. DOI: 10.1007/s00340-010-4278-1
- [18] Hajima R, Hayakawa T, Shizuma T, *et al.* Application of laser Compton scattered gamma-ray beams to nondestructive detection and assay of nuclear material. Eur Phys J-Spec Top, 2014, 223: 1229–1236. DOI: 10.1140/epjst/e2014-02177-y
- [19] Milburn R H. Electron scattering by an intense polarized photon field. Phys Rev Lett, 1963, 10: 75–77. DOI: 10.1103/Phys-RevLett.10.75
- [20] Arutyunyan F R and Tumanyan V A. The Compton effect on relativistic electrons and the possibility of obtaining high energy beams. Phys Lett, 1963, 4: 176–178. DOI: 10.1016/0031-9163(63)90351-2
- [21] Kulikov O F, Telnov Y Y, Filippov E I, *et al.* Compton effect on moving electrons. Phys Lett, 1964, **13**: 344–346. DOI: 10.1016/0031-9163(64)90040-X
- Bemporad C, Milburn R H, Tanaka N, *et al.* High-energy photons from Compton scattering of light on 6.0-GeV electrons. Phys Rev, 1965, **138**: B1546–B1549. DOI: 10.1103/Phys-Rev.138.B1546
- Ballam J, Chadwick G B, Gearhart R, *et al.* Total and partial photoproduction cross section at 1.44, 2.8, and 4.7 GeV. Phys Rev Lett, 1967, 23: 498–501. DOI: 10.1103/Phys-RevLett.23.498
- [24] Federici L, Giordano G, Matone G, *et al.* Backward Compton scattering of laser light against high-energy electrons: the LADON photon beam at Frascati. Nuovo Cimento Lett, 1980, 27: 339. DOI: 10.1007/BF02721314
- [25] Sandorfi A M, LeVine M J, Thorn C E, et al. High energy gamma ray beams from Compton backscattered laser light. IEEE T Nucl Sci, 1984, **30**: 3083–3087. DOI: 10.1109/TNS.1983.4336577
- [26] Weller H R and Ahmed M W. The HIγS facility: a freeelectron laser generated γ-ray beam for research in nuclear physics. Mod Phys Lett A, 2003, 18: 1569–1590. DOI: 10.1142/9789812777218_0023
- [27] Babusci D, Casano L, D'Angelo A, *et al.* Project GRAAL: the scientific case. Nuovo Cimento A, 1990, **103**: 1555–1576. DOI: 10.1007/BF02820302
- [28] Kezerashvili G Ya, Milov A M, Muchnoi N Yu, *et al.* A Compton source of high energy polarized tagged γ-ray beams. The ROKK-1M facility. Nucl Instrum Meth B, 1998, **145**: 40–48. DOI: 10.1016/S0168-583X(98)00266-3
- [29] Nakano T, Ejiria H, Fujiwara M, et al. New projects at Spring-8 with multi-GeV polarized photons. Nucl Phys A, 1998, 629: 559c-566c. DOI: 10.1016/S0375-9474(97)00737-9
- [30] Nakano T, Ahn J K, Fujiwara M, et al. Multi-GeV laserelectron photon project at SPring-8. Nucl Phys A, 2001, 684:

71c-79c. DOI: 10.1016/S0375-9474(01)00490-0

- [31] Ohgaki H, Toyokawa H, Kudo K, *et al.* Generation and application of Laser-Compton gamma-ray at ETL. Nucl Instrum Meth A, 2000, **455**: 54–59. DOI: 10.1016/S0168-9002(00)00693-8
- [32] Kaneyasu T, Takabayashi Y, Iwasaki Y, et al. Generation of laser Compton gamma-rays in the SAGA light source storage ring. Nucl Instrum Meth A, 2011, 659: 30–35. DOI: 10.1016/j.nima.2011.08.047
- [33] Taira Y, Adachi M, Zen H, *et al.* Generation of energy-tunable and ultra-short-pulse gamma rays via inverse Compton scattering in an electron storage ring. Nucl Instrum Meth A, 2011, 652: 696–700. DOI: 10.1016/j.nima.2010.08.036
- [34] Amano S, Horikawa K, Ishihara K, *et al.* Several-MeV γ ray generation at NewSUBARU by laser Compton backscattering. Nucl Instrum Meth A, 2009, **602**: 337–341. DOI: 10.1016/j.nima.2009.01.010
- [35] Muramatsu N, Kon Y, Daté S, *et al.* Development of high intensity laser-electron photon beams up to 2.9 GeV at the SPring-8 LEPS beamline. Nucl Instrum Meth A, 2014, **737**: 184–194. DOI: 10.1016/j.nima.2013.11.039
- [36] Ahmed M W, Champagne A E, Howell C R, et al. HIGS2: The next generation Compton γ-ray source. Aug. 31, 2012. http://www.phy.duke.edu/rps/higs2_prospectus_31aug2012.pdf
- [37] Ahn J K and Kim E S. Design study of the Compton backscattering photon beam facility at the Pohang light source. Nucl Instrum Meth A, 2004, 528: 600–604. DOI: 10.1016/j.nima.2004.04.110
- [38] Taín J L and Lallena A M (Eds). Proposal for the construction of a Gamma-ray beam line at the Spanish Synchrotron ALBA. December 2004. https://intranet.cells.es/static/Gamma_rays.pdf
- [39] Wurtz W A. Considerations for the construction of a gammaray beamline at the Canadian Light Source. Canadian Light Source, Apr. 22, 2010.
 - http://physics.usask.ca/ chang/department/Wurtz.pdf
- [40] Annand J R M, Fissum K G, Briscoe W J, et al. A laser back scattering facility at the MAX-IV laboratory. Jan. 27, 2012. https://www.maxlab.lu.se/sites/default/files/MAX-IV-WP3.pdf
- [41] Alesini D, Chaikovska I, Variola A, et al. DAΦNE gamma-rays factory. INFN-14-07/LNF, Apr. 1, 2014. arxiv: 1405.0861
- [42] Pan Q Y, Xu W, Luo W, *et al.* A future laser Compton scattering (LCS) γ-ray source: SLEGS at SSRF. Synchrotron Radiation News, 2009, **22**: 11–20. DOI: 10.1080/08940880902959759
- [43] Sprangle P, Ting A, Esarey E, *et al.* Tunable, short pulse hard X-rays from a compact laser synchrotron source. J Appl Phys, 1992, **72**: 5032–5038. DOI: 10.1063/1.352031
- [44] Pogorelsky I V, Ben-Zvi I, Hirose T, *et al.* Demonstration of 8×10^{18} photons/second peaked at 1.8 A in a relativistic Thomson scattering experiment. Phys Rev ST Accel Beams, 2000, **3**: 090702. DOI: 10.1103/PhysRevSTAB.3.090702
- [45] Gibson D J, Anderson S G, Barty C P J, et al. PLEIADES: A picosecond Compton scattering x-ray source for advanced backlighting and time-resolved material studies. Phys Plasmas, 2004, 11: 2857–2864. DOI: 10.1063/1.1646160
- [46] Hartemann F V, Tremaine A M, Anderson S G, *et al.* Characterization of a bright, tunable, ultrafast Compton scattering X-ray source. Laser Part Beams, 2004, 22: 221–244. DOI: 10.1017/S0263034604223059
- [47] Jochmann A, Irman A, Lehnert U, et al. Operation of a picosecond narrow-bandwidth Laser-Thomson backscattering Xray source. Nucl Instrum Meth B, 2013, **309**: 214–217. DOI: 10.1016/j.nimb.2013.01.065
- [48] Kuroda R, Toyokawa H, Yasumoto M, et al. Quasi-

monochromatic hard X-ray source via laser Compton scattering and its application. Nucl Instrum Meth A, 2011, **637**: S183–S186. DOI: 10.1016/j.nima.2010.04.001

- [49] Sakaue K, Washio M, Araki S, *et al.* Observation of pulsed xray trains produced by laser-electron Compton scatterings. Rev Sci Instrum, 2009, 80: 123304. DOI: 10.1063/1.3272789
- [50] Urakawa J. Development of a compact X-ray source based on Compton scattering using a 1.3 GHz superconducting RF accelerating linac and a new laser storage cavity. Nucl Instrum Meth A, 2011, 637: S47–S50. DOI: 10.1016/j.nima.2010.02.019
- [51] Du Y, Yan L, Hua J, et al. Generation of first hard X-ray pulse at Tsinghua Thomson Scattering X-ray Source. Rev Sci Instrum, 2013, 84: 053301. DOI: 10.1063/1.4803671
- [52] Kneissl U, Pitz H H and Zilges A. Investigation of nuclear structure by resonance fluorescence scattering. Prog Part Nucl Phys, 1996, 37: 349–443. DOI: 10.1016/0146-6410(96)00055-5
- [53] Pietralla N, Berant Z, Litvinenko V N, *et al.* Parity measurements of nuclear levels using a Free-Electron-Laser generated γ-ray beam. Phys Rev Lett, 2002, 88: 012502. DOI: 10.1103/PhysRevLett.88.012502
- [54] Gibson D J, Albert F, Anderson S G, et al. Design and operation of a tunable MeV-level Compton-scattering-based γ-ray source. Phys Rev ST Accel Beams, 2010, 13: 070703. DOI: 10.1103/PhysRevSTAB.13.070703
- [55] Albert F, Anderson S G, Gibson D J, *et al.* Characterization and applications of a tunable, laser-based, MeV-class Comptonscattering γ-ray source. Phys Rev ST Accel Beams, 2010, 13: 070704. DOI: 10.1103/PhysRevSTAB.13.070704
- [56] Albert F, Anderson S G, Anderson G A, *et al.* Isotope-specific detection of low-density materials with laser-based monoenergetic gamma-rays. Opt Lett, 2010, **35**: 354–356. DOI: 10.1364/OL.35.000354
- [57] Pruet J, McNabb D P, Hagmann C A, *et al.* Detecting clandestine material with nuclear resonance fluorescence. J Appl Phys, 2006, **99**: 123102. DOI: 10.1063/1.2202005
- [58] Bertozzi W, Caggiano J A, Hensley W K, et al. Nuclear resonance fluorescence excitations near 2 MeV in ²³⁵U and ²³⁹Pu. Phys Rev C, 2008, **78**: 041601(R). DOI: 10.1103/Phys-RevC.78.041601
- [59] Albert F, Anderson S G, Gibson D J, et al. Design of narrowband Compton scattering sources for nuclear resonance fluorescence. Phys Rev ST Accel Beams, 2011, 14: 050703. DOI: 10.1103/PhysRevSTAB.14.050703
- [60] Albert F, Hartemann F V, Anderson S G, et al. Precision linac and laser technologies for nuclear photonics gamma-ray sources. Phys Plasmas, 2012, 19: 056701. DOI: 10.1063/1.3695021
- [61] Habs D, Tajima T and Zamfir V. Extreme light infrastructure– nuclear physics (ELI-NP): New horizons for photon physics in Europe. Nuclear Physics News, 2011, 21: 23–29. DOI: 10.1080/10619127.2010.529741
- [62] Adriani O, Albergo S, Alesini D, et al. Technical Design Report: EuroGammaS proposal for the ELI-NP Gamma beam System. arxiv: 1407.3669
- [63] Rosner G. NuPECC long range plan 2010–Perspectives of nuclear physics in Europe. Nucl Phys News, 2011, 21: 3–4. DOI: 10.1080/10619127.2011.554754
- [64] Zhao Z T, Chen S Y, Yu L H, et al. THPC053: Shanghai soft Xray free electron laser test facility. Proceedings of IPAC2011, San Sebastian, Spain, 2011, 3011–3013.
- [65] Esarey E, Ride S K and Sprangle P. Nonlinear Thomson

scattering of intense laser pulses from beams and plasmas. Phys Rev E, 1993, **48**: 3003–3021. DOI: 10.1103/Phys-RevE.48.3003

- [66] Lau Y Y, He F, Umstadter D P, *et al.* Nonlinear Thomson scattering: A tutorial. Phys Plasmas, 2003, **10**: 2155–2162. DOI: 10.1063/1.1565115
- [67] Brau C A. Oscillations in the spectrum of nonlinear Thomsonbackscattered radiation. Phys Rev ST Accel Beams, 2004, 7: 020701. DOI: 10.1103/PhysRevSTAB.7.020701
- [68] Li D G, Yokoya K, Hirose T, *et al.* Transition probability and polarization of final photons in nonlinear Compton scattering for linearly polarized laser. Japanese Journal of Applied Physics, 2003, **42**: 5376–5382. DOI: 10.1143/JJAP.42.5376
- [69] Seipt D and Kämpfer B. Nonlinear Compton scattering of ultrashort intense laser pulses. Phys Rev A, 2011, 83: 022101. DOI: 10.1103/PhysRevA.83.022101
- [70] Seipt D and Kämpfer B. Scaling law for the photon spectral density in the nonlinear Thomson-Compton scattering. Phys Rev ST Accel Beams, 2011, 14: 040704. DOI: 10.1103/Phys-RevSTAB.14.040704
- [71] Hartemann F V, Albert F, Siders C W, et al. Low-intensity nonlinear spectral effects in Compton scattering. Phys Rev Lett, 2010, 105: 130801. DOI: 10.1103/PhysRevLett.105.130801
- [72] Albert F, Anderson S G, Gibson D J, et al. Three-dimensional theory of weakly nonlinear Compton scattering. Phys Plasmas, 2011, 18: 013108. DOI: 10.1063/1.3536457
- [73] Hartemann F V and Wu S S Q. Nonlinear brightness optimization in Compton scattering. Phys Rev Lett, 2013. 111: 044801. DOI: 10.1103/PhysRevLett.111.044801
- [74] Maroli C, Petrillo V, Tomassini P, et al. Nonlinear effects in Thomson backscattering. Phys Rev ST Accel Beams, 2013, 16: 030706. DOI: 10.1103/PhysRevSTAB.16.030706
- [75] Hartemann F V, Brown W J, Gibson D J, et al. Highenergy scaling of Compton scattering light sources. Phys Rev ST Accel Beams, 2005, 8: 100702. DOI: 10.1103/Phys-RevSTAB.8.100702
- [76] Petrillo V, Baccia A, Ben Alì Zinatib R, *et al.* Photon flux and spectrum of γ-rays Compton sources. Nucl Instrum Meth A, 2012, **693**: 109–116. DOI: 10.1016/j.nima.2012.07.015
- [77] Luo W, Xu W, Pan Q Y, et al. A 4D Monte Carlo laser-Compton scattering simulation code for the characterization of the future energy-tunable SLEGS. Nucl Instrum Meth A, 2011, 660: 108–115. DOI: 10.1016/j.nima.2011.09.035
- [78] Agostinelli S, Allison J, Amako K, *et al.* Geant4-a simulation toolkit. Nucl Instrum Meth A, 2003, **506**: 250–303. DOI: 10.1016/S0168-9002(03)01368-8
- [79] User's Manual of CAIN. http://lcdev.kek.jp/ yokoya/CAIN/
- [80] Luo W, Yang L F and Xu B J. SLEGS@SSRF. Shanghai Synchrotron Radiation Facility, 2010. (in Chinese)
- [81] He W B, Ma Y G, Cao X G, *et al.* Giant dipole resonance as a fingerprint of α clustering configurations in ¹²C and ¹⁶O. Phys Rev Lett, 2014, **113**: 032506. DOI: 10.1103/Phys-RevLett.113.032506
- [82] Tao C, Ma Y G, Zhang G Q, et al. Symmetry energy dependence of the pygmy and giant dipole resonances in an isospin dependent quantum molecular dynamics model. Nucl Sci Tech, 2013, 24: 030502. DOI: 10.13538/j.1001-8042/nst.2013.03.001
- [83] Ye S Q, Cai X Z, Fang D Q, et al. Systematic study of dynamical dipole mode via the isospin-dependent Boltzmann-Uehling-Uhlenbeck model. Nucl Sci Tech, 2014, 25: 030501. DOI: 10.13538/j.1001-8042/nst.25.030501
- [84] Wang F P, Shen S F and Yan Y P. Theoretical investigation on

PROPOSAL FOR A HIGH BRIGHTNESS

the triggered gamma-ray emission from long-lived isomer in ¹⁷⁸Hf. Nucl Sci Tech, 2014, **37**: 080502. (in Chinese) DOI: 10.11889/j.0253-3219.2014.hjs.37.080502

- [85] Xu Y, Xu W, Ma Y G, *et al.* A new study for ${}^{16}O(\gamma, \alpha){}^{12}C$ at the energies of nuclear astrophysics interest: The inverse of key nucleosynthesis reaction ${}^{12}C(\alpha, \gamma){}^{16}O$. Nucl Instrum Meth A, 2007, **581**: 866-873. DOI: 10.1016/j.nima.2007.08.078
- [86] Chen J G, Xu W, Wang H W, et al. A potential phototransmutation of fission products triggered by Compton backscattering photons. Nucl Instrum Meth A, 2009, **599**: 118– 123. DOI: 10.1016/j.nima.2008.10.031
- [87] Ginzburg I F, Kotkin G L, Serbo V G, *et al.* Colliding γ -e and γ - γ beams based on the single-pass e⁺-e⁻ colliders (VLEPP type). Nucl Instrum Meth, 1983, **205**: 47–68. DOI: 10.1016/0167-5087(83)90173-4
- [88] Telnov V I. Comments on photon colliders for Snowmass 2013. arxiv: 1308.4868v1
- [89] Ferrario M, Alesini D, Alessandroni M, et al. IRIDE: Interdisciplinary research infrastructure based on dural electron linacs and lasers. Nucl Instrum Meth A, 2014, 740: 138-146. DOI: 10.1016/j.nima.2013.11.040
- [90] Pike O J, Mackenroth, Hill E G, et al. A photon-photon collider in a vacuum hohlraum. Nat Photonics, 2014, 8: 434–436. DOI: 10.1038/nphoton.2014.95
- [91] Baldwin G C, Solem J C and Gol'danskii V I. Approaches to the development of gamma-ray lasers. Rev Mod Phys, 1981, 53: 687–744. DOI: 10.1103/RevModPhys.53.687
- [92] Rivlin L A. Nuclear gamma-ray laser: the evolution of the idea. Quantum Electronics, 2007, 37: 723–744. DOI: 10.1070/QE2007v037n08ABEH013541

- [93] Olariu S, Popescu I I and Collins C B. Amplification of gamma radiation from X-ray excited nuclear states. arXiv: nucl-ex/9907010v1
- [94] Dupraz K, Cassou K, Delerue N, *et al.* Design and optimization of a highly efficient optical multipass system for γ-ray beam production from electron laser beam Compton scattering. Phys Rev ST Accel Beams, 2014, **17**: 033501. DOI: 10.1103/Phys-RevSTAB.17.033501
- [95] Rykovanov S G, Geddes C G R, Vay J-L, et al. Quasimonoenergetic femtosecond photon sources from Thomson Scattering using laser plasma accelerators and plasma channels. J Phys B, 2014, 47: 234013. DOI: 10.1088/0953-4075/47/23/234013
- [96] Xu T, Chen M, Li F Y, et al. Spectrum bandwidth narrowing of Thomson scattering X-rays with energy chirped electron beams from laser wakefield acceleration. Appl Phys Lett, 2014, 104: 013903. DOI: 10.1063/1.4861594
- [97] Ghebregziabher I, Shadwick B A and Umstadter D. Spectral bandwidth reduction of Thomson scattered light by pulse chirping. Phys Rev ST Accel Beams, 2013, 16: 030705. DOI: 10.1103/PhysRevSTAB.16.030705
- [98] Terzić B, Deitrick K, Hofler A S, et al. Narrow-band emission in Thomson sources operating in the high-field regime. Phys Rev Lett, 2014, 112: 074801. DOI: 10.1103/Phys-RevLett.112.074801
- [99] Seipt D, Rykovanov S G, Surzhykov A, et al. Narrowband inverse Compton scattering X-ray sources at high laser intensities. Phys Rev A, 2015, 91: 033402. DOI: 10.1103/Phys-RevA.91.033402